

Product Profile

- Modular design minimizes operator visual obstruction
- Small size and flexible mounting
- Shock, temperature and environmental protection
- Configurable according to user requirements
- Supports industry standard communications and 2.4 GHz or 802.11b 11Mbps radio



2 4 5 5 VEHICLE MOUNT COMPUTER

The 2455 is a versatile, high performance and economical solution for data collection applications using industrial vehicles such as forklift trucks and stock pickers.

The two piece design of the terminal allows the operator to separate the display and keyboard or conventionally mount as one unit. The modularity and small size easily adapts to space constraints common with today's smaller forklifts. Unique bracket design on the terminal provides unlimited viewing angle and positioning choices.

Industrial casing protects the terminal from dust, dirt and rain. The 2455 can tolerate very cold temperatures outdoors or usage in freezers. Wide ranging power supply options make installation in virtually all industrial vehicles easy. The 2455 is built to sustain real-world conditions

such as constant shock, vibrations and power fluctuations common to industrial vehicles.

The terminal integrates with most common host environments, either directly to the network, or through a data collection server which provides additional network management benefits. IBM and VT terminal emulation eliminates the need to re-program host applications. In addition, TCP/IP network support provides similar ease of integration in client/server environments.

The 2455 incorporates 2.4 GHz and 802.11b 11Mbps radio support for wide area coverage and interference immunity and interoperability with other WLI Forum OpenAir products.

Physical Characteristics

Display Unit: 28.4 x 15.2 x 10.7cm (11.2" x 6" x 4.2") 4.04kg (8.9lbs)
Keyboard: 28.4 x 10.4 x 4.3cm (11.2" x 4.1" x 1.7") 1kg (2.2lbs)
Power Supply: 16.5 x 11.4 x 2.5cm (6.5" x 4.5" x 1") .73kg (1.6lbs)

Environment

Operating Temperature:
Standard Unit: -10° to +50°C (14° to 122°F)
Cold Temperature Option:
 -30° to +50°C (-22° to 122°F)
Storage Temperature:
 -20° to 60°C (-4° to 140°F)
Humidity: 10 to 90% non-condensing
Shock & Vibration: Vibration tested to SAE J-1399 Class 2, MIL STD 810D
Sealing: Sealed against dust and moisture to IP66

Power

Primary: 12V to 80VDC universal power supply with surge, over-voltage, and reversal protection
Memory Backup: Rechargeable NiCad

Memory

RAM Memory: 1MB
Non-volatile Memory: 2MB Option for 2MB additional, 4MB total
Extended Storage: 2, 4MB SRAM

Interfaces

Local Device Communications:
 Auxiliary RS-232
Laser Scanners: 10-pin connector for use with Intermec cabled & wireless laser scanners

- Optical Serial Interface
- RS232-C up to 38.4 baud
- XMODEM, YMODEM for data transfer
- Supports Configurable Serial Protocol and XON/OFF

Display

Full Screen: 25 lines by 80 characters or configurable oversized characters including 13 x 80, 25 x 40, or 13 x 40
Display Options: Transmissive LCD CGA display for standard environments
 EL (electroluminescent) CGA display for cold or bright locations

Keyboard

Layout: ABCD keyboard layout with five function keys, oversized numeric keypad

- F1-F10 function keys also available on display unit
- Standard PC-AT keyboard interface for optional keyboards (req. adapter cable)
- Options for U.S. Multilingual, European, IBM 5250, IBM 3270, and ANSI/VT

Software

Programmable: Microsoft C
Terminal Emulation: IBM 3270 and 5250 SNA and TELNET, ANSI/VT, TN5250, TN3270, Screen Mapping
Web-based: dcBrowser™ for HTML applications

Connectivity

- DHCP Client
- Direct TCP/IP Support
- Sockets interface or terminal emulation
- Network Ethernet or Token Ring

Integrated RF Module

Frequency: 2.4 GHz frequency band, actual frequencies in use vary by country
 WLI Forum OpenAir
Type: Frequency Hopping Spread Spectrum
Data Rate: 1.6 Mbps, .8 Mbps fallback
Range*: From 1500+ ft (450+ m) to 500 ft (150 m) depending on environment

IEEE 802.11b Wi-Fi Certified

Type: Direct Sequence Spread Spectrum
Data Rate: 11/5.5/2/1 Mbps with Auto fallback for increased range
Range* at 1 Mbps: From 1750 ft (533 m) to 165 ft (50 m) depending on environment
Range* at 11 Mbps: From 525 ft (160 m) to 80 ft (24 m) depending on environment
Security: Wired Equivalent Privacy (WEP) - 64 or 128 bit encryption
 *Unlimited range with roaming

Host Support via DCS 300 Server

Host Environment: IBM AS400, 5/390, Digital, HP, Unix, Windows NT
Connectivity: Ethernet, Token Ring, 100BaseT, Twinax, Coax, SDLC
Communications: TCP/IP, SNA

Accessories

Desktop stand, Desktop power supply, User's Manual, Programmer's Software Kit (PSK)

Regulatory Approvals

FCC - Part 15.247 Certified, Canada - RSS 210 Certified, ETS 300 328 Type Approved, EN 55022 / CISPR 22 Class B, FCC Part 15 & ICES-003 Class A, SCT Certified, NOM - EM-121, AS 3548 - C tick Marked, Compliant with all European Directives, CE Marked (ETS 300 826), UL Listed, UL 1950, C22.2 #950 & IEC 60529-IP54, TUV GS Licensed, EN 60950 & EN 60529 - IP54, NYCE Certified, NOM 19

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.



North America
Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

Systems & Solutions
 550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies
 9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Canada
 7065 Tranmere Drive
 Mississauga, Ontario
 L5S 1M2 Canada
 tel: 905.673.9333
 fax: 905.673.3974

**Europe/
 Middle East & Africa**
Headquarters
 Sovereign House
 Vastern Road
 Reading RG1 8BT
 United Kingdom
 tel: 44.118.987.9400
 fax: 44.118.987.9401

Asia
Asia Regional Office
 26-16 International Plaza
 10 Anson Road
 Singapore 079903
 tel: 65.6324.8391
 fax: 65.6324.8393

Intermec International Inc
 14 Floor, IBM-Pacific Century Place
 2A Workers Stadium
 Chaoyang District, Beijing 100027
 P.R. China
 Tel: +86 (010).6539 1012
 Fax: +86 (010).6539 1025

Australia
 Level 7, 200 Pacific Highway
 Crows Nest, NSW 2065
 Australia
 tel: 61.2.9492.4400
 fax: 61.2.9954.6300

South America & Mexico
Intermec South America Ltda.
 Rua Arandu 1544-15 andar
 Edificio Itavera
 Brooklin Novo 04562-031
 Sao Paulo, SP
 Brazil
 tel: 55.11.5501.2070

Intermec Technologies de Mexico
 Av Tamaulipas #141, Primer Piso
 Col. Hipodromo Condesa
 Mexico, DF, 06140 Mexico
 tel: 525.55.211.1919
 fax: 525.55.211.8121

Worldwide
Fax Document
Retrieval Service
 800.755.5505
 (North America Only)
 tel: 650.556.8447

Internet
 www.intermec.com

Sales
 800.347.2636
 (toll free in N.A.)
 tel: 425.348.2726

Service and Support
 800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Intermec
 e x p e c t MORE™

Copyright © 2004 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611030-01E 04/04

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.