

Falcon® 4400 Series

Windows® Based Mobile Computer

Data Sheet



Features

- Choice of Microsoft® Windows Mobile® or Windows® CE Operating Systems
- Supports 802.11b and 802.11g Radios
- Standard/Long Range/Advanced Long Range Integrated Laser Scanner, or Linear/2D Imager Options
- Keypad options include 26-key, 48-key, 52-key, and 5250 emulation versions
- Ergonomic Design
- Rugged design survives multiple 5 ft / 15 M drops to concrete
- Tethered Stylus provides enhanced stylus security
- Intel® XScale™ PXA255 400MHz
- Bright 64K Color TFT Active Matrix QVGA display
- Industry leading beeper volume
- Instant-On Trigger (Falcon 4420 Only)

Accessories

- Powered Vehicle Dock
- Single-Slot Dock and Four-Slot Dock
- Four-Slot Battery Charger
- Handle/Handstrap Conversion Kit
- Holsters/Softcases
- USB Data Cable
- Serial Charging Cable
- Serial Printer Adapter



The Falcon 4400 Series has tested compatible with Cisco's wireless solution. The Cisco Compatible logo signifies that PSC's product has undergone interoperability testing by PSC together with Cisco and a third-party test house based on testing criteria set by Cisco. PSC is solely responsible for the support and warranty of its product. Cisco makes no warranties, express or implied, with respect to PSC's product or its inter-operation with the listed Cisco product(s) and disclaims any implied warranties of merchantability, fitness for a particular use or against infringement.



Copyright © PSC Inc. 2004-2006. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from PSC. PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. Falcon, and the PSC logo are registered trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners. Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com. Product specifications are subject to change without notice.

Mechanical

Dimensions

Length: 9.0" / 22.6 cm Width at display: 3.5" / 8.6 cm
Width at grip: 2.5" / 6.4 cm Height at grip: 1.6" / 4.1 cm

Weight: 23.3 oz / 724 g (Will vary depending upon the configuration selected. Falcon 4400 model shown with radio, scanner, and battery pack)

Display: 3.5" active matrix TFT QVGA display, 320 x 240, pixels; 64K colors

Indicators: Good read LED; scan LED

Keypads: 26-Key Standard Alphanumeric; 48-Key (handed version only) Full Alphanumeric and 5250 support; 52-Key Full Alphanumeric and 5250 support

Construction: Industrial, polycarbonate/ABS-blend plastic shell with thermoplastic urethane overmold

Environmental

Temperature Rating

Operating: 14° to 122° F / -10° to 50° C
Storage: -13° to 158° F / -25° to 70° C

Humidity: 5 to 95% NC

Shock: Multiple 5.0' / 15 M drops to concrete

Water & Dust: IEC529, Rating IP54DW

Optical	Laser Scan Engine		Linear Imager	2D Imager
	SR*	LR*/ALR*		
Light Source	650 nm	650 nm	645 nm	626 nm
Scan Rate	35 ± 5 scans/sec.	35 ± 5 scans/sec.	36 ± 5 scans/sec.	N/A
Ambient Light Immunity				
Artificial Light	4,844 Lux	4,844 Lux	100,000 Lux	N/A
Sunlight	86,112 Lux	86,112 Lux	100,000 Lux	100,000 Lux

* Key: SR = Standard Range, LR = Long Range, ALR = Advanced Long Range.

DEPTH OF FIELD TABLE Typical Range Comparisons					
Label Density	Laser Scan Engine			Linear Imager	2D Imager
	SR*	LR*	ALR*		
5 mil UPCA	30-50'/ 8-13 cm	—	—	30-50'/ 8-13 cm	—
75 mil	2.5-90'/ 6-23 cm	—	—	—	—
8 mil	—	—	—	—	2.5-6.6'/ 6-17 cm
10 mil	2.5-13.0'/ 6-33 cm	1.5-24'/ 39-61 cm	—	1.5-70'/ 4-18 cm	2.1-8.0'/ 5-20 cm
13 mil Code 39	—	—	15.0-45.0'/ 38-114 cm	1.5-80'/ 4-20 cm	2.5-12.5'/ 6-32 cm
15 mil Code 39	2.5-19'/ 6-48 cm	9-33'/ 23-84 cm	20-50'/ 5H27 cm	—	2.1-8.8'/ 5-33 cm
15 mil Data Matrix	—	—	—	—	2.3-9.2'/ 6-23 cm
15 mil QR Code	—	—	—	—	3.1-7.8'/ 8-20 cm
20 mil Code 39	10-29'/ 3-74 cm	11-47'/ 28-119 cm	—	1.5-11.5'/ 4-29 cm	—
30 mil Code 39	—	—	32-85'/ 81-216 cm	—	—
35 mil MaxiCode	—	—	—	—	2.1" / 5-28 cm
40 mil Code 39	2.5-30'/ 6-76 cm	1.3-83'/ 33-211 cm	—	30-150' / 8-38 cm	—
55 mil Code 39	40-45'/ 10-114 cm	16-100'/ 41-254 cm	26-100'/ 66-254 cm	—	—
70 mil (reflective)	—	47-199'/ 119-505 cm	113-249'/ 287-632 cm	—	—
100 mil (reflective)	—	59-240'/ 150-610 cm	124-350'/ 315-889 cm	—	—

* Key: SR = Standard Range, LR = Long Range, ALR = Advanced Long Range. Minimum distance determined by symbol length and scan angle. Dependent upon printing resolution, contrast, and ambient light.

System

Operating System: Windows® CE v4.2 or v5.0, Windows Mobile® v5.0

Microprocessor: Intel® XScale™ PXA255, 400 MHz

Memory

Windows® CE: RAM: 64 MB or 128 MB; Flash: 64 MB
Windows Mobile®: RAM: 64 MB; Flash: 64 MB

Dock Communications: USB 1.1 (ActiveSync) & RS-232 (ActiveSync and other RS-232 protocols)

PC Card: Internal PC Card Type I/II slot

Beep Tone: 86dBA (at 24" / 61cm) / 100dBA (at 10 cm) (typical)
Programmable for pitch and duration

Power Options

Rechargeable Lithium Ion Battery Pack (2000 mAh)
Falcon Single and Four-Slot Dock with power supply
Advanced Power Management: (without PC Card & backlight):
Sleep/off mode with programmable timeout: 5 mA; Idle mode: 60 mA (typical); Operating mode: 155 mA (typical). Rechargeable lithium backup battery; Low battery indicator (display icon)

Radio Support

Windows® CE: 802.11b or 802.11g
Windows Mobile®: 802.11g

System Support: VT100/220, HP700/92, IBM 3270/5250 terminal emulators; Browser support via Microsoft® Internet Explorer; TCP/IP Communications

Management Tools: Falcon Desktop Utility (FDU) for security & configuration. Falcon Management Utility (FMU) or Wavelink® Avalanche for remote device management & software distribution.

Development Environments:

Windows® CE: Embedded Visual C++, Visual C# .NET, Visual Basic .NET, Personal Java 1.1, Java Virtual Machine (JVM), Falcon® CE Developers Toolkit, and Wavelink® Studio.
Windows Mobile®: Visual Studio 2005 and Wavelink® Studio.

Decoding Capability (auto-discrimination)†

1D Codes

- Code 32, 39, 93
- EAN/JAN 8, 13
- Matrix 2/5
- EAN/UPC 2 digit ext.
- Codabar
- EAN 128
- MSI / Plessey
- EAN/UPC 5 digit ext.
- Code 128
- UPCA, E
- Standard 2/5
- EAN/UCC Composite
- Code 128 ext.
- Interleaved 2/5
- Code 39 Full ASCII
- RSS-14/RSS Limited

2D Codes

- PDF-417
- RSS Expanded
- Data Matrix
- QR Code
- Micro PDF-417
- Aztec Code
- Maxi Code
- OCR-A/B
- U.S. Currency Serial Number
- MICR E 13 B
- Postal Codes

† Please refer to the appropriate Product Reference Guide (PRG) for specific symbology support for the laser scan engine or imaging scan engine options.

Safety and Regulatory

Electrical: EN60950, UL60950, CSA60950

Battery: IATA/UN

Emissions: FCC Part 15C, EN55022, VCCI, ICES-003, CNS 13438, AS/NZS 3548

Radio: FCC Part 15.247, EN 300 328

Laser Classification: CDRH Class II;

(CAUTION: Laser Radiation—do not stare into beam); IEC 60825-1, Class 2, Class 3R for ALR devices

Restriction of Hazardous Substances: Complies to EU RoHS



PSC Inc.

959 Terry Street
Eugene OR 97402-9150 USA
Tel: 800 695 5700 or 541 683 5700
Fax: 541 345 7140

www.psc.com

