

6300 Series Direct Part Mark (DPM) Imagers

6300 DPM Corded 6320 DPM Cordless



 powered by
Adaptus™
imaging technology 5.0

Features

Powered by Adaptus™ Imaging Technology 5.0 – the world's leading technology brand for image-based bar code reading

Custom DPM illumination system creates readable images from all marks

Custom DPM decoding engine assures the highest reading yield on DPM codes

Rugged, ergonomic design ensures best-of-class durability

Autodiscriminates reading of 1D and 2D codes

Omni-directional reading of DPM codes delivers superior performance regardless of mark orientation

Available in corded and cordless models

The 6300 DPM Series of handheld imagers sets the industry standard for reading Direct Part Mark (DPM) codes for part traceability.

DPM identification for part traceability demands rugged, self-contained imagers that perform consistently on all types of codes and parts. The 6300 DPM Series offers the only imagers in the industry that read everything from the most challenging DPM codes to the easiest printed bar codes. And, these imagers are designed to hold up to the harshest environments. When you add Hand Held Products' outstanding ergonomics and durability to the list of breakthrough features, these imagers are the clear choice for customers who demand best-in-class performance from their DPM solutions.

The 6300 DPM Series includes the 6300 corded and 6320 cordless models. Both models are powered by Adaptus™ Imaging Technology 5.0 – the world's leading technology brand for image-based bar code reading.

The 6300 DPM Series supports USB, keyboard wedge, and RS-232 communications; while the 6320 cordless model uses Bluetooth® communications to connect to an intelligent base station. Both imagers offer a high-resolution image sensor and simple setup interface.

The Adaptus™ Imaging Technology platform allows the 6300 DPM imagers to optimally illuminate marks of any type, on any surface. Low-angle lighting with quadrant control provides the uniform illumination required for dot peen and etch marks. The integrated diffuser provides soft illumination required for highly reflective parts such as electrochemical etched marks on shiny, round surfaces. Diffused bright field illumination provides uniform lighting throughout a wide working range, which is ideal for 1D bar code labels and marks located on recessed surfaces.

6300 DPM Series Specifications

Lighting/Optics Performance

Illumination:	Integrated diffuser; bright- and dark-field LEDs			
Aiming:	Horizontal green light bar aimed at the center field of view			
Reading Direction:	Omni-directional, pitch and skew (off-axis) angles up to 34 degrees			
Working Range:	5 mil (.013cm)	10 mil (.025cm)	15 mil (.038cm)	20 mil (.050cm)
Near	0 in. (0cm)	0 in. (0cm)	0 in. (0cm)	0 in. (0cm)
Far	1.4 in. (3.6cm)	2.1 in. (5.5cm)	3.0 in. (7.6cm)	3.8 in. (9.5cm)

Mechanical/Electrical

Dimensions

Length:	3.3 in. (8.4cm)		
Height:	6.9 in. (17.5cm)		
Width:	5.3 in. (13.4cm)		
Weight:	Model 6300: 9.5 oz. (270 g)		
	Model 6320 with Battery: 11.6 oz. (330 g)		Base Station: 8.8 oz. (250 g)

Power

Electrical Requirements:	Model 6300: 5 VDC
	Model 6320: 5 VDC
Battery (6320):	Eight hours normal use fully charged at 77°F (25°C)

Image

Sensor:	1280 x 960 high-resolution pixel array
----------------	----------------------------------------

Data Input/Output

Trigger:	Via trigger switch in the handle or via PC Software (presentation mode)
Additional Outputs:	Multifunctional LED and beeper to indicate good read, device status, or errors

Interfaces

Model 6300:	USB and/or RS-232 for data communication, set-up, and image review. PS2 keyboard wedge, PS2 or USB keyboard emulation
Model 6320:	Reader to base station: Bluetooth (Class 2) 33 ft. (10m) range Base station to PC: USB/RS-232/PS2

Environmental

Temperature

Operating:	Model 6300: 14°F to +122°F (-10°C to +50°C) Model 6320: 32°F to +122°F (0°C to +50°C)
Storage:	Model 6300: -40°F to +158°F (-40°C to +70°C) Model 6320: -40°F to +140°F (-40°C to +60°C)
Humidity:	0 to 95%, non-condensing
Sealing:	Reader IP54 Base Station IP41
Mechanical Shock:	Model 6300: Operational after 50 drops from 6.5 ft. (2m) to concrete Model 6320: Operational after 25 drops from 6.5 ft. (2m) to concrete
Agency:	CE, FCC, UL, and CSA
Warranty:	18 months
Radio Certification:	US, Canada, EU

Symbologies

2 Dimensional:	Data Matrix, QR Code
Linear:	EAN13, UPC-A, EAN8, UPC-E, Interleaved 2 of 5, Code 39, Code 128, Code 93

Worldwide Offices

Offices Serving North America
Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 582 4263
napresales@handheld.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
napresales@handheld.com

Offices Serving Europe, Middle East, and Africa
Europe
Tel: +31 (0) 40 29 01 600
eupresales@handheld.com
United Kingdom
Tel: +44 (0) 1 925 240055
eupresales@handheld.com
Italy
Tel: +39 (0) 2 67 100752
eupresales@handheld.com

France
Tel: +33 (0) 1 41 158220
eupresales@handheld.com
Germany
Tel: +49 (0) 7 477 151377
eupresales@handheld.com
Spain
Tel: +34 93 228 78 68
eupresales@handheld.com

Offices Serving Asia and the Pacific Rim
Hong Kong
Tel: +852 2511 3050
appresales@handheld.com
Japan
Tel: +813 5770 6312
appresales@handheld.com
Shanghai
Tel: +86 21 6361 3818
appresales@handheld.com

Offices Serving Latin America
Naples, Florida
Tel: +1 239 263 7600
lapresales@handheld.com
São Paulo
Tel: +55 11 2178 0500
lapresales@handheld.com
Rio De Janeiro
Tel: +55 21 2178 0500
lapresales@handheld.com
Mexico
Tel: +52 55 5203 2100
lapresales@handheld.com

Web Site Address www.handheld.com

Hand Held Products, Inc., ("Hand Held Products") © 1999-2006. All rights reserved. Printed in the U.S.A.
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.